

VALVE OPERATORS

LEVER OPERATORS - VICEROY™

- A. Valves shall be provided with 7 position latch lock handles.
- B. Latch lock handles shall be constructed of PVC and shall include a spring loaded lever for position lock.
- C. Lever shall be capable of holding the disc in any of the locking positions with no movement up to the full pressure rating of the valve.

-OR-

LEVER OPERATORS DOMINION™

- A. Valves shall be provided with 6 position latch lock handles.
- B. Latch lock handles shall be constructed of epoxy coated cast aluminum and shall include a spring loader lever for position lock.
- C. Lever shall be capable of holding the disc in any of the locking positions with no movement up to the full pressure rating of the valve.

GEAR OPERATORS

- A. Valves shall be provided with infinite position gear operators.
- B. Gear case (body) shall be constructed of cast iron painted internally and externally for maximum protection.
- C. Enclosure shall be sealed to IP65 and maintenance free.
- D. Self locking gearing shall be capable of holding the disc in any position with no movement up the full pressure rating of the valve.
- E. Gear operator shall provide 90° of travel with $\pm 5^\circ$ adjustment in closed position.
- F. Gear operator shall include a non-corrosive sealed indicator for remote visibility.
- G. Gear operator shall include manual adjustment capabilities.